

Peppol BIS3 order



Card	BCE	Name	Description	Value
1..1	M	ubl:Order	Namespace	urn:oasis:names:specification:ubl:schema:xsd:Order-2
1..1	M	cbc:CustomizationID	Specification identification <i>Identifies the specification of content and rules that apply to the transaction.</i>	Fixed value: urn:fdc:peppol.eu:poacc:trns:order:3
1..1	M	cbc:ProfileID	Business process type identifier <i>Identifies the BII profile or business process context in which the transaction appears.</i>	Fixed value:urn:fdc:peppol.eu:poacc:bis:ordering:3
1..1	M	cbc:ID	Order identifier <i>A transaction instance must have an identifier. The identifier enables referencing the transaction for various purposes such as from other transactions that are part of the same process.</i>	Example: PO12345
0..1	N	cbc:SalesOrderID	Sales order reference <i>An identifier of a referenced sales order, issued by the Seller.</i>	Example: SO98765
1..1	M	cbc:IssueDate		Example: 2024-04-24
0..1	N	cbc:IssueTime		Example: 09:46:39

Card	BCE	Name	Description	Value
1..1	M	cbc:OrderTypeCode	Order type code <i>Indicates whether the order is a Purchase order (tir01-153), Consignment order (tir01-p050), Blanket order (tir01-p051) or Call of order (tir01-p052). Default is purchase order. See section Order Type Code in BIS-documentation for handling of order types.</i>	Codes: 220 <u>Order</u> Document/message by means of which a buyer initiates a transaction with a seller involving the supply of goods or services as specified, according to conditions set out in an offer, or otherwise known to the buyer. 221 <u>Blanket order</u> Usage of document/message for general order purposes with later split into quantities and delivery dates and maybe delivery locations. 226 <u>Call off order</u> Document/message to provide split quantities and delivery dates referring to a previous blanket order. 227 <u>Consignment order</u> Order to deliver goods into stock with agreement on payment when goods are sold out of this stock.
0..1	N	cbc:Note	Response clarification <i>Clarification of the suppliers decision.</i>	
1..1	M	cbc:DocumentCurrencyCode	Currency <i>The default currency for the order.</i>	Example: EUR
0..1	N	cbc:CustomerReference	Buyer contact <i>The element is used for the reference of who ordered the products/services. Example being the name of the person ordering, employee number or a code identifying this person or department/group. Also known as "Buyer reference", and should also be sent in the corresponding invoice.</i>	Example: ABC123

Card	BCE	Name	Description	Value
1..1	N	cbc:AccountingCost	Buyers accounting string <i>Used by the buyer to specify a reference that should be repeated in e.g. invoice to enable the buyer to automatically book e.g. to the right project, or account.</i>	Example: 1234:45435:243234
0..1	N	cac:ValidityPeriod	Validity period	
1..1	N	cbc:EndDate	Order validity end date <i>The end date for when the order is valid. The end date for the time period within which the seller must respond. An order should contain the validity end date</i>	Example: 2018-06-02
0..1	N	cac:QuotationDocumentReference	Quotation reference <i>Reference to quotation which is basis for the order</i>	
1..1	N	cbc:ID	Quotation document reference <i>A requirement to give a unique reference to the quotation that is the base for the order.</i>	Example: 1232424
0..1	N	cac:OrderDocumentReference	Order reference	
1..1	N	cbc:ID	Order document reference <i>Used to reference the initial order that was rejected and a new order is issued.</i>	Example: 4832423
0..1	N	cac:OriginatorDocumentReference	Originator document	
1..1	N	cbc:ID	Originator document reference <i>A reference to Originator Document. To be able to give a reference to the internal requisition on the buyer site on which the order is based.</i>	Example: 5435235
0..1	N	cac:CatalogueReference	Order reference	
1..1	N	cbc:ID	Catalogue reference <i>A reference to the Catalogue on which this Order is based.</i>	Example: Cat2023-03-07
0..1	N	cac:AdditionalDocumentReference	Additional documents	
1..1	N	cbc:ID	Document identifier <i>An identifier for the referenced document.</i>	Example: doc-34
0..1	N	cbc:DocumentType	Document description <i>Textual description of the document.</i>	Example: Timesheet
0..1	N	cac:Attachment	Attachment(s)	
0..1	N	cbc:EmbeddedDocumentBinaryObj	Attached document <i>The attached document embeded as binary object, coded as Base64. The binary object has two supplementary components: a Mime Code, which specifies the Mime type of the attachment and a Filename that is provided by (or on behalf of) the sender of the document</i>	Example: QkITIE9yZGVyIEFncmVlbWVudCAtIDQyQQ==

Card	BCE	Name	Description	Value
M	N @mimecode	Attached document Mime code <i>The mime code of the attached document.</i>	Example: application/vnd.openxmlformats-officedocument.spreadsheetml.sheet
M	N @filename	Attached document filename <i>The file name of the attached document</i>	Example: Hours-spent.xml
0..1	N	... cac:ExternalReference	External reference <i>Reference to external document</i>	
1..1	N cbc:URI	External document URI <i>The Uniform Resource Identifier (URI) that identifies where the external document is located.</i>	Example: http://www.test.eu/image.jpg
0..1	N	. cac:Contract	Contract information <i>Reference to contract</i>	
1..1	N	.. cbc:ID	Reference identifier <i>Positive identification of the reference such as a unique identifier.</i>	
0..1	N	. cac:ProjectReference	Project Reference	
1..1	N	.. cbc:ID	Project reference <i>The identification of the project the order refers to.</i>	Example: PID33
1..1	M	. cac:BuyerCustomerParty	Buyer information	
1..1	M	.. cac:Party	Description of buyer	
1..1	M	... cbc:EndpointID	Buyer party electronic address <i>Identifies the seller party's electronic address</i>	Example: 7300010000001
M	M @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..n	M	... cac:PartyIdentification	Buyer identification	
1..1	M cbc:ID	Buyer party identification <i>An identification for the buyer party.</i>	Example: 7300010000001
M	M @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..1	M	... cac:PartyName	Party identification	
1..1	M cbc:Name	Buyer name <i>Name of buyer The name of the party who orders the listed items.</i>	Example: Buyer name
0..1	M	... cac:PostalAddress	Postal address <i>Postal address of the buyer</i>	
0..1	M cbc:StreetName	Address line 1 <i>The main address line in a postal address usually the street name and number.</i>	

Card	BCE	Name	Description	Value
0..1	N cbc:AdditionalStreetName	Address line 2 An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.	
0..1	M cbc:CityName	City The common name of the city where the postal address is. The name is written in full rather than as a code.	
0..1	M cbc:PostalZone	Post code The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.	
0..1	O cbc:CountrySubentity	Country subdivision For specifying a region, county, state, province etc. within a country by using text.	
0..1	N cac:AddressLine	Address Line	
0..1	N cbc:Line	Address line 3 <i>An additional address line in an address that can be used to give further details supplementing the main line.</i>	Example: Gate 34
1..1	M cac:Country	Country	
1..1	M cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	M	... cac:PartyTaxScheme	Buyer tax information	
1..1	M cbc:CompanyID	Buyer TAX identifier <i>The buyers registered Value Added Tax identifier. To be stated in case reverse charge is to apply to the purchase.</i>	
1..1	M cac:TaxScheme	Tax scheme	
1..1	M cbc:ID	Tax scheme identifier. E.g. "VAT" or "GST"	Example: VAT or GST
1..1	M	... cac:PartyLegalEntity	Buyer legal information	
1..1	M cbc:RegistrationName	Buyers legal registration name <i>The official name of the party as registered with the relevant fiscal authority.</i>	
0..1	N cbc:CompanyID	Buyers legal registration identifier <i>Identifies a company as registered with the company registration scheme.</i>	Example: 987654321

Card	BCE	Name	Description	Value
	N @schemeID	Scheme identifier <i>The identification scheme identifier of the buyer legal registration identifier.</i>	Example: 0002
0..1	N cac:RegistrationAddress	Legal address	
0..1	N cbc:CityName	Buyers legal registration address city name <i>Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village.</i>	
1..1	N cac:Country	Country	
1..1	N cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	O	... cac:Contact	Contact Information <i>Buyer contact information</i>	
0..1	O cbc:Name	Contact person name <i>The name of the contact person.</i>	
0..1	N cbc:Telephone	Contact telephone number <i>A phone number for the contact person. If the person has a direct number, this is that number.</i>	
0..1	N cbc:ElectronicMail	Contact email address <i>The e-mail address for the contact person. If the person has a direct e-mail this is that email.</i>	Example: purchase@buyer.com
1..1	M	. cac:SellerSupplierParty	Seller information <i>Description of seller</i>	
1..1	M	.. cac:Party	Description of seller	
1..1	M	... cbc:EndpointID	Seller party electronic address <i>Identifies the seller party's electronic address</i>	Example: 7300010000001
M	M @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..n	M	... cac:PartyIdentification	Party identification	
1..1	M cbc:ID	Seller party identification <i>An identification for the seller party.</i>	Example: 7300010000001
M	M @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..1	M	... cac:PartyName	Party name <i>Name of seller</i>	

Peppol BIS3 order



Card	BCE	Name	Description	Value
1..1	M cbc:Name	Seller party trading name <i>The trading name of the party.</i>	Example: Seller name
0..1	M	... cac:PostalAddress	Postal address <i>Postal address of the seller</i>	
0..1	M cbc:StreetName		
0..1	O cbc:AdditionalStreetName		
0..1	M cbc:CityName		
0..1	M cbc:PostalZone		
0..1	O cbc:CountrySubentity		
0..1	M cac:AddressLine	Address Line	
0..1	O cbc:Line	Address line 3 <i>An additional address line in an address that can be used to give further details supplementing the main line.</i>	Example: Gate 34
1..1	M cac:Country	Country	
1..1	M cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
1..1	M	... cac:PartyLegalEntity	Seller legal information	
1..1	M cbc:RegistrationName	Seller legal registration name <i>The official name of the party as registered with the relevant fiscal authority.</i>	
0..1	N cbc:CompanyID	Seller legal registration identifier <i>Identifies a company as registered with the company registration scheme.</i>	Example: 987654321
O	N @schemeID	Scheme identifier <i>The identification scheme identifier of the seller legal registration identifier.</i>	Example: 0002
0..1	N cac:RegistrationAddress	Legal address	
0..1	N cbc:CityName	Seller legal registration address city name <i>Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village.</i>	
1..1	N cac:Country	Country	

Card	BCE	Name	Description	Value
1..1	N cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	N	... cac:Contact	Contact Information <i>Seller contact information</i>	
0..1	N cbc:Name	Contact person name <i>The name of the contact person.</i>	
0..1	N cbc:Telephone	Contact telephone number <i>A phone number for the contact person. If the person has a direct number, this is that number.</i>	
0..1	N cbc:ElectronicMail	Contact email address <i>The e-mail address for the contact person. If the person has a direct e-mail this is that email.</i>	Example: sales@seller.com
0..1	N	. cac:OriginatorCustomerParty	Originator party <i>Information regarding the originator of the order</i>	
1..1	N	.. cac:Party	Party information <i>Description of the originator party</i>	
0..n	N	... cac:PartyIdentification	Party identification <i>Identification of the originator</i>	
1..1	N cbc:ID	Originator identifier <i>Identifies a party.</i>	Example: 7300010000001
0	N @schemeID	Scheme identifier <i>Scheme identifier for party identification</i>	Example: 0088
0..1	N	... cac:PartyName	Party name <i>Name of the originator</i>	
1..1	N cbc:Name	Originator name <i>The name of the party.</i>	Example: Originator name
0..1	N	... cac:Contact	Contact Information <i>The originators contact information</i>	
0..1	N cbc:Name	Contact person name <i>The name of the contact person.</i>	
0..1	N cbc:Telephone	Contact telephone number <i>A phone number for the contact person. If the person has a direct number, this is that number.</i>	

Card	BCE	Name	Description	Value
0..1	N cbc:ElectronicMail	Contact email address <i>The e-mail address for the contact person. If the person has a direct e-mail this is that email.</i>	Example: sales@seller.com
1..1	N	. cac:AccountingCustomerParty	Invoicee party <i>Information regarding the receiver of the invoice based on the order (Invoicee)</i>	
1..1	N	.. cac:Party	Party information <i>Description of the invoicee party</i>	
1..1	N	... cbc:EndpointID	Seller party electronic address <i>Identifies the seller party's electronic address</i>	Example: 7300010000001
M	N @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..n	N	... cac:PartyIdentification	Party identification <i>Identification of the invoicee party</i>	
1..1	N cbc:ID	Invoicee identifier <i>An identifier for the invoicee party.</i>	Example: 7300010000001
M	N @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..1	N	... cac:PartyName	Party name	
1..1	N cbc:Name	Invoicee name <i>The name of the party who should be invoiced for the ordered items (invoicee).</i>	Example: Invoicee name
0..1	N	... cac:PostalAddress	Postal address <i>Postal address of the invoicee</i>	
0..1	N cbc:StreetName	Address line 1 <i>The main address line in a postal address usually the street name and number.</i>	Example: The main address line in the postal address, usually the street name and number
0..1	N cbc:AdditionalStreetName	Address line 2 <i>An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.</i>	
0..1	N cbc:CityName	City <i>The common name of the city where the postal address is. The name is written in full rather than as a code.</i>	

Card	BCE	Name	Description	Value
0..1	N cbc:PostalZone	Post code <i>The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.</i>	
0..1	N cbc:CountrySubentity	Country subdivision <i>For specifying a region, county, state, province etc. within a country by using text.</i>	
0..1	N cac:AddressLine	Address Line	
0..1	N cbc:Line	Address line 3 <i>An additional address line in an address that can be used to give further details supplementing the main line.</i>	Example: Gate 34
1..1	N cac:Country	Country	
1..1	N cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	N	... cac:PartyTaxScheme	Party tax scheme <i>Tax information of the invoicee party</i>	
1..1	N cbc:CompanyID	Invoicee TAX identifier <i>The invoicees registered Value Added Tax identifier</i>	
1..1	N cac:TaxScheme	Tax scheme	
1..1	N cbc:ID	Mandatory element. E.g. "VAT" or "GST"	Example: VAT or GST
1..1	N	... cac:PartyLegalEntity	Party legal entity <i>Legal information of the invoicee party</i>	
1..1	N cbc:RegistrationName	Invoicee's Legal registration name <i>The official name of the invoicee party as registered with the relevant fiscal authority.</i>	
0..1	N cbc:CompanyID	Company identifier <i>Identifies a company as registered with the company registration scheme.</i>	Example: 987654321
O	N @schemeID	Buyer legal registration identifier identification scheme identifier <i>The identification scheme identifier of the buyer legal registration identifier.</i>	
0..1	N cac:RegistrationAddress	Legal registration address	
0..1	N cbc:CityName	City name <i>Associates with the registered address of the party within a Corporate Registration Scheme. The name of a city, town, or village.</i>	
1..1	N cac:Country	Country	

Card	BCE	Name	Description	Value
1..1	N cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	N	... cac:Contact	Contact Information <i>Invoicee contact information</i>	
0..1	N cbc:Name	Contact person name <i>The name of the contact person.</i>	
0..1	N cbc:Telephone	Contact telephone number <i>A phone number for the contact person. If the person has a direct number, this is that number.</i>	
0..1	N cbc:ElectronicMail	Contact email address <i>The e-mail address for the contact person. If the person has a direct e-mail this is that email.</i>	Example: sales@seller.com
0..1	M	. cac:Delivery	Delivery information	
1..1	M	.. cac:DeliveryLocation	Delivery location	
1..1	M	... cbc:ID	Delivery location ID <i>An identifier for the location to where the ordered items should be delivered.</i>	Example: 7300010000001
M	M @schemeID	Scheme identifier <i>Scheme identifier for the electronic address</i>	Example: 0088
0..1	O	... cbc:Name	Delivery location name <i>A name of the location to where the ordered items should be delivered.</i>	Example: South side goods arrival dock
0..1	O	... cac:Address	Delivery address	
0..1	O cbc:StreetName	Address line 1 <i>The main address line in a postal address usually the street name and number.</i>	
0..1	O cbc:AdditionalStreetName	Address line 2 <i>An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.</i>	
0..1	O cbc:CityName	City <i>The common name of the city where the postal address is. The name is written in full rather than as a code.</i>	

Card	BCE	Name	Description	Value
0..1	O	cbc:PostalZone	Post code <i>The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.</i>	
0..1	O	cbc:CountrySubentity	Country subdivision <i>For specifying a region, county, state, province etc. within a country by using text.</i>	
0..1	O	cac:AddressLine	Address Line	
0..1	O	cbc:Line	Address line 3 <i>An additional address line in an address that can be used to give further details supplementing the main line.</i>	Example: Gate 34
1..1	O	cac:Country	Country	
1..1	O	cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	M	cac:RequestedDeliveryPeriod	Requested delivery period	
0..1	M	cbc:StartDate	Period start date <i>The date on which the period starts. The start dates counts as part of the period. Format = "YYYY-MM-DD"</i>	Example: 2024-04-24
0..1	N	cbc:StartTime	Period start time <i>The time at which this period begins. Format = "hh:mm:ss"</i>	Example: 12:30:00
0..1	M	cbc:EndDate	Period end date <i>The date on which the period ends. The end date counts as part of the period. Format = "YYYY-MM-DD"</i>	Example: 2024-04-25
0..1	N	cbc:EndTime	Period end time <i>The time at which this period end. Format = "hh:mm:ss"</i>	Example: 18:00:00
0..1	M	cac:DeliveryParty	Delivery party	
0..1	M	cac:PartyIdentification	Party identification <i>Identification of the delivery party. The party to whom the goods are delivered</i>	
1..1	M	cbc:ID	Delivery party identifier <i>In this BIS: The identifier of the party that should receive the ordered items</i>	Example: 987654321
O	M	@schemeID	Deliver party registration identifier identification scheme identifier <i>The identification scheme identifier of the deliverparty identifier.</i>	Example: 0002
1..1	M	cac:PartyName	Party name	

Peppol BIS3 order



Card	BCE	Name	Description	Value
1..1	M	cbc:Name	Delivery party name <i>In this BIS: The name of the party that should receive the delivery</i>	Example: Surgery department
0..1	M	cac:PostalAddress	Final Delivery address <i>The final address for the delivery</i>	
0..1	M	cbc:StreetName	Address line 1 <i>The main address line in a postal address usually the street name and number.</i>	
0..1	O	cbc:AdditionalStreetName	Address line 2 <i>An additional address line in a postal address that can be used to give further details supplementing the main line. Common use are secondary house number in a complex or in a building.</i>	
0..1	M	cbc:CityName	City <i>The common name of the city where the postal address is. The name is written in full rather than as a code.</i>	
0..1	M	cbc:PostalZone	Post code <i>The identifier for an addressable group of properties according to the relevant national postal service, such as a ZIP code or Post Code.</i>	
0..1	O	cbc:CountrySubentity	Country subdivision <i>For specifying a region, county, state, province etc. within a country by using text.</i>	
0..1	O	cac:AddressLine	Address Line	
0..1	O	cbc:Line	Address line 3 <i>An additional address line in an address that can be used to give further details supplementing the main line.</i>	Example: Gate 34
1..1	M	cac:Country	Country	
1..1	M	cbc:IdentificationCode	Country code <i>A code that identifies the country. The lists of valid countries are registered with the ISO 3166-1 Maintenance agency, "Codes for the representation of names of countries and their subdivisions". Codes must be according to the alpha-2 representation.</i>	Example: NL
0..1	N	cac:Contact	Contact Information <i>Invoicee contact information</i>	
0..1	N	cbc:Name	Contact person name <i>The name of the contact person.</i>	

Card	BCE	Name	Description	Value
0..1	N	cbc:Telephone	Contact telephone number <i>A phone number for the contact person. If the person has a direct number, this is that number.</i>	
0..1	N	cbc:ElectronicMail	Contact email address <i>The e-mail address for the contact person. If the person has a direct e-mail this is that email.</i>	
0..1	N	cac:Shipment	Shipment	
1..1	N	cbc:ID	Shipment identifier <i>Element is mandated by syntax structure use value NA</i>	
0..1	N	cbc:ShippingPriorityLevelCode	Requested shipping priority <i>The priority level requested by the buyer for the shipping of the order. Use value: "1" for Express/urgent/rush.</i>	Example: 1
0..1	N	cac:TransportHandlingUnit	Transport handling unit	
0..1	N	cbc:ShippingMarks	Packing label <i>A text that the buyer requests to be printed on the packing labels.</i>	Example: Receiving instructions.
0..1	N	cac:DeliveryTerms	Terms of delivery	
0..1	N	cbc:ID	Delivery terms identifier <i>Delivery terms identifier, normally Incoterms</i>	Example: FOB
0..1	N	cbc:SpecialTerms	Delivery special terms <i>A description of special conditions relating to the Delivery Terms.</i>	
0..1	N	cac:DeliveryLocation	Delivery location information	
1..1	N	cbc:ID	Delivery terms location <i>The location to which the delivery terms refer. Used to qualify the delivery terms e.g. "Terms of delivery are FOB Rotterdam"</i>	Example: Rotterdam
0..1	N	cac:PaymentTerms	Payment terms	
1..1	N	cbc:Note	Payment terms <i>Payment terms for the order described in text</i>	
0..n	N	cac:AllowanceCharge		
1..1	N	cbc:ChargeIndicator		
0..1	N	cbc:AllowanceChargeReasonCode	Document level allowance or charge reason code <i>The reason for the document level allowance or charge, expressed as a code. For allowances a subset of codelist UNCL5189 is to be used, and for charges codelist UNCL7161 applies. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason</i>	Example: 95

Card	BCE	Name	Description	Value
1..1	N	.. cbc:AllowanceChargeReason	Allowance and charges reason <i>A textual reason for the allowance or the charge. Can also be its name. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason</i>	
0..1	N	.. cbc:MultiplierFactorNumeric	Document level allowance or charge percentage <i>The percentage that may be used, in conjunction with the document level allowance base amount, to calculate the document level allowance or charge amount. To state 20%, use value 20.</i>	Example: 20
1..1	N	.. cbc:Amount	Allowance and charge amount <i>The net amount of the allowance or the charge excluding TAX.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cbc:BaseAmount	Document level allowance or charge base amount <i>The base amount that may be used, in conjunction with the document level allowance or charge percentage, to calculate the document level allowance or charge amount. Must be rounded to maximum 2 decimals</i>	Example: 1000
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cac:TaxCategory	Tax category	
1..1	N	... cbc:ID	TAX category code <i>The TAX category code that applies to the document level allowance or charge.</i>	Example: S
0..1	N	... cbc:Percent	TAX rate <i>The TAX rate, represented as percentage that applies to the document level allowance or charge. As this element is of data type percentage, please note that no %-sign should be used. To state 22 %, use value 22.00</i>	Example: 22.00
1..1	N	... cac:TaxScheme	Tax scheme information	
1..1	N cbc:ID	Tax scheme identifier. E.g. "VAT" or "GST"	Example: VAT or GST
0..1	N	. cac:TaxTotal	Tax total <i>Specification of expected tax amount</i>	
1..1	N	.. cbc:TaxAmount	TAX total amount <i>The total TAX amount that is "added to the document total w/o TAX". This is the sum of all TAX subcategory amounts. The expected Tax Total in the corresponding invoice</i>	Example: 200

Card	BCE	Name	Description	Value
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	. cac:AnticipatedMonetaryTotal	Anticipated monetary total <i>Estimated total amounts for the order</i>	
1..1	N	.. cbc:LineExtensionAmount	Sum of line amounts <i>Sum of line amounts in the document. The total of Line Extension Amounts net of tax and settlement discounts. Must be rounded to maximum 2 decimals.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cbc:TaxExclusiveAmount	Document total without TAX <i>The "Sum of line amounts" plus "sum of allowances on document level" plus "sum of charges on document level". Must be rounded to maximum 2 decimals.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cbc:TaxInclusiveAmount	Document total including TAX <i>The total value including TAX. Must be rounded to maximum 2 decimals.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cbc:AllowanceTotalAmount	Sum of allowances on document level <i>Sum of all allowances on header level in the document. Allowances on line level are included in the line amount and summed up into the "sum of line amounts". Must be rounded to maximum 2 decimals.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	.. cbc:PayableRoundingAmount	Rounding of document total <i>The amount to be added to the total to round the amount to be paid. Must be rounded to maximum 2 decimals.</i>	Example: 200

Card	BCE	Name	Description	Value
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
1..1	N	.. cbc:PayableAmount	Payable amount <i>The amount that is expected to be paid. Must be rounded to maximum 2 decimals.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
1..n	M	. cac:OrderLine	Order line <i>Specification of order lines</i>	
0..1	O	.. cbc:Note	Order line note <i>Free-form text applying to the Order Line. This element may contain notes or any other similar information that is not contained explicitly in another structure. Is to capture any free form description related to the order line as a whole.</i>	
1..1	M	.. cac:LineItem	Line item <i>Description of line item</i>	
1..1	M	... cbc:ID	Line item identifier <i>Identifies the Line Item assigned by the buyer, the identifier must be unique within the order.</i>	Example: 1
1..1	M	... cbc:Quantity	Ordered quantity <i>The quantity of Items for the Line Item. The quantity for the order line.</i>	Example: 1000
M	M @unitCode	Ordered quantity unit of measure <i>The unit of measure that applies to the ordered quantity.</i>	
1..1	M	... cbc:LineExtensionAmount	Order line amount <i>The total amount for the Line Item, including Allowance Charges but net of taxes. The expected line amount excluding TAX but inclusive of other charges, allowances and taxes.</i>	Example: 200
M	M @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N	... cbc:PartialDeliveryIndicator	Partial delivery indicator <i>Indicates if the line items must be delivered in a single shipment. Default is that partial delivery is allowed (true)</i>	Default: true

Card	BCE	Name	Description	Value
0..1	N	... cbc:AccountingCost	Buyers accounting string <i>The buyer's accounting information applied to the Line Item, expressed as text.</i>	
0..1	N	... cac:Delivery	Line delivery information <i>Delivery information for the order line</i>	
0..1	N cbc:ID	Delivery location ID <i>An identifier for the location to where the ordered line item should be delivered.</i>	Example: 7300010000001
O	N @schemeID	Deliver to location identifier identification scheme identifier <i>The identification scheme identifier of the Deliver to location identifier.</i>	Example: 0088
1..1	M cac:RequestedDeliveryPeriod		
0..1	O cbc:StartDate	Period start date <i>The date on which the period starts. The start dates counts as part of the period.Format = "YYYY-MM-DD"</i>	Example: 2024-04-24
0..1	N cbc:StartTime	Period start time <i>The time at which this period begins. Format = "hh:mm:ss"</i>	Example: 12:30:00
0..1	N cbc:EndDate	Period end date <i>The date on which the period ends. The end date counts as part of the period.Format = "YYYY-MM-DD"</i>	Example: 2024-04-25
0..1	N cbc:EndTime	Period end time <i>The time at which this period end. Format = "hh:mm:ss"</i>	Example: 18:00:00
0..1	N	... cac:OriginatorParty	Originator information <i>Information regarding the originator of the order line</i>	
0..n	N	... cac:PartyIdentification	Party identification <i>Identification of the originator</i>	
1..1	N cbc:ID	Order line originator party ID <i>The party who originated Order.</i>	Example: 7300010000001
O	N @schemeID	Scheme identifier <i>Scheme identifier for party identification</i>	Example: 0088
0..1	N	... cac:PartyName	Party name <i>Name of the originator</i>	
1..1	N cbc:Name	Order line originator party name <i>The party who originated Order.</i>	Example: Originator name
0..n	O	... cac:AllowanceCharge	Order line allowance and charges <i>A group of business terms providing information about allowances or charges applicable to the individual order line.</i>	

Card	BCE	Name	Description	Value
1..1	O	cbc:ChargeIndicator	Use "true" when informing about Charges and "false" when informing about Allowances	Example: false
0..1	O	cbc:AllowanceChargeReasonCode	Line level allowance or charge reason code The reason for the line level allowance or charge, expressed as a code. For allowances a subset of codelist UNCL5189 is to be used, and for charges codelist UNCL7161 applies. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason	Example: 95
0..1	O	cbc:AllowanceChargeReason	Line level allowance or charge reason The reason for the line level allowance or charge, expressed as text. The Document level allowance reason code and the Document level allowance reason shall indicate the same allowance reason	Example: Discount
0..1	N	cbc:MultiplierFactorNumeric	Line level allowance or charge percentage The percentage that may be used, in conjunction with the line level allowance base amount, to calculate the line level allowance or charge amount.	Example: 20
1..1	M	cbc:Amount	Line level allowance or charge amount The amount of an allowance or a charge, without TAX. Must be rounded to maximum 2 decimals	Example: 200
M	N	@currencyID	Currency identifier Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.	Example: EUR
0..1	N	cbc:BaseAmount	Line level allowance or charge base amount The base amount that may be used, in conjunction with the line level allowance or charge percentage, to calculate the line level allowance or charge amount. Must be rounded to maximum 2 decimals	Example: 1000
M	N	@currencyID	Currency identifier Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.	Example: EUR
0..1	M	cac:Price	Price information	
1..1	M	cbc:PriceAmount	Item price The net price of the item including all allowances, charges and taxes but excluding TAX. Although price is an optional element in an order it recommended as best practice to either state the price or provide reference to an appropriate source from which the price can be identified such as a contract, catalogue or a quote.	Example: 211.124

Card	BCE	Name	Description	Value
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N cbc:BaseQuantity	Item price base quantity <i>The actual quantity to which the price applies.</i>	Default: 1
O	N @unitCode	Base quantity unit of measure <i>The unit of measure that applies to the base quantity.</i>	Example: H87 (= Piece)
0..1	N cac:AllowanceCharge	Price discount information <i>Information on discounts connected to the price</i>	
1..1	N cbc:ChargeIndicator	AllowanceChargeIndicator <i>Only discounts are allowed for the price, hence the only valid value is false (meaning an allowance)</i>	Fixed: false
1..1	N cbc:Amount	Discount amount <i>Discount amount connected to the price</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
0..1	N cbc:BaseAmount	Item list price <i>The gross price of the item before subtracting discounts. E.g. list price.</i>	Example: 200
M	N	... @currencyID	Currency identifier <i>Currency identifier, value must be the same as what is used in tir01-007, DocumentCurrencyCode.</i>	Example: EUR
1..1	M	... cac:Item	Item information	
0..1	N cbc:Description	Item description <i>Free-form field that can be used to give a text description of the item. A detailed description of the item.</i>	
1..1	M cbc:Name	Item name <i>A short name for an item. A short name given to an item, such as a name from a Catalogue, as distinct from a description.</i>	
0..1	M cac:BuyersItemIdentification	Buyers item identification	
1..1	M cbc:ID	Buyers item identifier <i>An identifier, assigned by the buyer, for the item. Associates the item with its identification according to the buyer's system.</i>	Example: abc32432
0..1	O cac:SellersItemIdentification	Sellers item identification	

Card	BCE	Name	Description	Value
1..1	M cbc:ID	The Sellers item identifier <i>An identifier, assigned by the seller, for the item. Associates the item with its identification according to the seller's system.</i>	Example: 3249834
0..1	N cac:ManufacturersItemIdentification	Manufacturers Item Identifier	
1..1	N cbc:ID	Manufacturers Item Identifier <i>An identifier, assigned by the items manufacturer, for the item.</i>	Example: manid659
0..1	O cac:StandardItemIdentification	Standard item identification	
1..1	M cbc:ID	Item standard identifier <i>An item identifier based on a registered scheme. Associates the item with its identification according to a standard system.</i>	Example: 05704066204093
M	M @schemeID	Item standard identifier identification scheme identifier <i>The identification scheme identifier of the Item standard identifier</i>	Fixed: 0160
0..n	N cac:ItemSpecificationDocumentRef	Item specification reference <i>Referece to an item specification document</i>	
1..1	N cbc:ID	Document reference identifier <i>Reference to an external document (ID) when it is necessary to specify the details of the item.</i>	Example: doc4353.pdf
0..n	N cac:CommodityClassification	Commodity classification information	
0..1	N cbc:ItemClassificationCode	Item classification code <i>A code for classifying the item by its type or nature. Classification codes are used to allow grouping of similar items for a various purposes e.g. public procurement (CPV), e-Commerce (UNSPSC) etc.</i>	Example: 9873242
M	N @listID	Item classification identifier identification scheme identifier <i>The identification scheme identifier of the Item classification identifier</i>	Example: STI
O	N @listVersionID	Item classification identifier version identification scheme identifier <i>The identification scheme version identifier of the Item classification identifier</i>	Example: 20.0602
O	N @name	Clear text name equivalent of classification code <i>The textual equivalent of the code value</i>	Example: Office furniture
0..1	N cac:ClassifiedTaxCategory	Line TAX information	
1..1	N cbc:ID	Item TAX category code <i>The TAX category code for the item.</i>	Example: S
0..1	N cbc:Percent	Line TAX rate <i>The TAX percentage rate that applies to the line amount.</i>	Example: 25
1..1	N cac:TaxScheme	Tax scheme information	
1..1	N cbc:ID	<i>Tax scheme. E.g. "VAT" or "GST"</i>	Example: VAT or GST

Card	BCE	Name	Description	Value
0..n	N cac:AdditionalItemProperty	Additional item property information <i>A group of business terms providing information about properties of the goods and services invoiced.</i>	
1..1	N cbc:Name	Item property name <i>The name of the property. The name must be sufficiently descriptive to define the value. The definition may be supplemented with the property unit of measure when relevant.</i>	Example: Color
0..1	N cbc:NameCode	Item property code <i>Code for the item property according to a property code system.</i>	
M	N @listID	Name code list id. <i>An identifier for the code list used for the Name code, this is bilaterally agreed</i>	
1..1	N cbc:Value	Item property value <i>The value of the item property.</i>	Example: Red
0..1	N cbc:ValueQuantity	Item property unit of measure <i>The unit of measure in which the property value is stated, if relevant. May not be relevant when properties are descriptive.</i>	Example: 10
M	N @unitCode	Value quantity unit of measure <i>The unit of measure that applies to the value quantity.</i>	Example: H87 (= Piece)
0..1	N cbc:ValueQualifier	Property classification <i>Standardized and predefined classification of items properties.</i>	
0..n	N cac:ItemInstance	Item instance information <i>Information relevant to an item instance or shared by the items in the order line.</i>	
0..1	N cbc:SerialID	Item serial identification <i>An identifier that is specific to the items in the order line.</i>	
0..1	N cac:LotIdentification	Item lot information <i>Information about the production lot which the order line items come from.</i>	
0..1	N cbc:LotNumberID	Item lot identifier <i>An identifier for the production lot which the order line items come from.</i>	